Appendix H Supplemental Information – Link Two

Appendix H-1 Vascular Plant Species Observed – Link Two

Vascular Plant Species Observed - Link Two

| Scientific Name | Common Name |
|------------------------------|---------------------------|
| Acacia constricta | whitethorn acacia |
| Acacia greggii | catclaw |
| Acalypha Acalypha | Cutciu II |
| neomexicana | |
| Acourtia nana | desert holly |
| Agave parryi | Parry's agave |
| | agave |
| Agave sp. Ambrosia dumosa | agave |
| | |
| Anaphalis | pearly everlasting |
| margaritacea | |
| Arctostaphylos | Madrone |
| pungens | .1 |
| Aristida purpurea | three-awn |
| Aristida ternipes | three-awn |
| Asclepias linaria | pine-needle milkweed |
| Atriplex canescens | fourwing saltbush |
| Baccharis salicifolia | seep willow |
| Baccharis | desert broom |
| sarothroides | desert broom |
| Baileya multiradiata | |
| Boemmeria hispida | |
| Bothriochloa barbinodes | cane bluestem |
| Bothryochloa marginatus | beardgrass |
| Bouteloua barbata | grama |
| Bouteloua curtipendula | sideoats grama |
| Bouteloua eriopodum | black grama |
| Brickellia sp. | brickelbush |
| Buchloe dactyloides | buffalograss |
| Calliandra conferta | false-mesquite calliandra |
| Calliandra eriophylla | fairy duster |
| Carnegiea gigantea | saguaro |
| Celtis spinosa | desert hackberry |
| Spreng. var. pallida | |
| Cercidium floridum | blue paloverde |
| Cercidium microphyllum | foothill paloverde |
| Cercidium spp. | Palo verde |
| Cheilanthes | lindheimer's lip fern |
| | |

| Scientific Name | Common Name |
|-------------------------------|-----------------------------|
| Isocoma tenuisecta | burroweed |
| Isocoma wrightii | burroweed |
| Juglans microcarpa | walnut |
| Juniperus cf. coahuilensis | roseberry |
| Kochia scoparia | |
| Koeberlinia spinosa | allthorn |
| Larrea tridentata | creosotebush |
| Lepidium alyssoides | |
| Lycium torreyi | |
| Machaeranthera riparia | |
| Mimosa biuncifera | wait-a-minute bush |
| Mollugo cerviana | |
| Muhlenbergia porteri | bushy muhly |
| Nolina microcarpa | beargrass |
| Notholaena sp. | |
| Opuntia chlorotica | pancake prickly pear |
| Opuntia engelmannii | Engelmann's prickly pear |
| Opuntia fulgida | jumping cactus |
| Opuntia leptocaulis | desert Christmas cholla |
| Opuntia phaeacantha | Sprawling prickly pear |
| Opuntia spinosior | cane cholla cactus |
| Opuntia spp. | Prickly pear cactus |
| Opuntia violacea Engelm. var. | purple prickly |
| macrocentra | pear |
| Panicum cf. antidotales | |
| Panicum sp. | Panic grass |
| Parkinsonia sp. | parkinsonia |
| Pellaea sp. | |
| Populus fremontii | Fremont's cottonwood |
| Proboscidea althaeifolia | sand devil's claw |
| Prosopis pubescens | screwbean mesquite |
| Prosopis glandulosa | honey mesquite |
| Psilostrophe cooperi | paper daisy |
| a diloditophic cooperi | paper daisy |

| Scientific Name | Common Name |
|---------------------|----------------------------|
| lindheimeri | |
| Chilopsis linearis | desert willow |
| Chloris virgata | fingergrass |
| Chrysothamnus | |
| pulchellus | southwest rabbitbrush |
| Commelina | 1 |
| dianthifolia | dayflower |
| Condalia spathulata | |
| Coryphantha | |
| vivipara | |
| Croton pottsii | leatherweed croton |
| Dasylirion wheeleri | sotol |
| Dasyochloa | |
| pulchella | fluffgrass |
| Datura wrightii | Indian apple |
| Dimorphocarpa | |
| wislizenii | |
| Echinocereus | hundla hadaahaa |
| fasciculatus | bundle hedgehog |
| Echinopedon | |
| wrightii | |
| Ephedra trifurca | long leaf ephedra; Mexican |
| | Mormon tea |
| Eragrostis | Lehman lovegrass; African |
| lehmanniana | lovegrass |
| Ericameria | turpentine bush |
| laricifolia | _ |
| Eurotia lanata | winter-fat |
| Ferocactus | barrel cactus |
| wislizenii | |
| Flourensia cernua | tarbush |
| Fouquieria | ocotillo |
| splendens | ocotino . |
| Gutierrezia | threadleaf snakeweed |
| microcephala | micadical blidic wood |
| Gutierrezia | snakeweed |
| sarothrae | |
| Heliotropium sp. | heliotrope |
| Hibiscus denudatus | hibiscus |
| Hilaria mutica | tobosa grass |

| Scientific Name | Common Name |
|------------------------|------------------------------------|
| D 1 | 1.1 |
| Psorothamnus scoparius | dalea |
| Quercus arizonica | Arizona scrub oak |
| Quercus emoryi | |
| Rhus microphylla | desert sumac |
| Rumex hymenosepalus | dock |
| Salix gooddingii | willow |
| Salix sp. | willow |
| Salsola australis | Russian thistle |
| Selaginella sp. | |
| Setaria leucophila | foxtail grass |
| Solanum eleagnifolium | purple nightshade |
| Sphaeralcea incana | |
| Sporobolis erioides | sporobolis |
| Sporobolus contractum | dropseed |
| Sporobolus giganteus | giant dropseed |
| Sporobolus airoides | alkali sacaton |
| Sporobolus cryptandrus | sand dropseed |
| Suaeda suffrutescens | shrubby seepweed |
| Tiquila canescens | |
| Xanthium strumarium | cocklebur |
| Yucca elata | soaptree yucca |
| Yucca baccata | datil yucca; |
| | banana yucca |
| Yucca torreyi | Torrey's yucca |
| Zinnia acerosa | spinyleaf zinnia; desert zinnia |
| Zinnia pumila | zinnia |

List of Wildlife Species Observed - Link Two

Appendix H-2 List of Wildlife Species Observed—Link Two

| Common Name | Scientific Name | Location |
|------------------------|---------------------------------|-----------------------------|
| | ARIZONA | |
| | Birds | |
| American kestrel | Falco sparverius | Grasslands |
| Black-throated sparrow | Amphispiza bilineata | TX Canyon |
| Blue-gray gnatcatcher | Polioptila caerulea | TX Canyon |
| Brown-headed cowbird | Molothrus ater | Agriculture |
| Cactus wren | Campylorhynchus brunneicapillus | East of Tucson |
| Cassin's finch | Carpodacus cassinii | TX Canyon |
| Chihuahuan raven | Corvus cryptoleucus | Ubiquitous |
| Cooper's hawk | Accipiter cooperii | TX Canyon |
| Curve-billed Thrasher | Toxostoma curvirostre | Cacti desert east of Tucson |
| Flycatcher | Empidonax sp. | TX Canyon |
| Field sparrow | Spizella pusilla | TX Canyon |
| Gambel's quail | Callipela californica | Ubiquitous |
| Greater roadrunner | Geococcyx californianus | Ubiquitous |
| Harris hawk | Parabuteo unicinctus | Grasslands |
| House sparrow | Passer domesticus | Benson-Tucson |
| Killdeer | Charadrius vociferous | Agriculture |
| Meadowlark | Sturnella neglecta | Ubiquitous |
| Mexican chickadee | Parus sclateri | Cacti desert |
| Morning dove | Zenaida macroura | Ubiquitous |
| Northern cardinal | Cardinalis cardinalis | TX Canyon, East of Willcox |
| Northern mockingbird | Mimus polyglottos | TX Canyon |
| Phainopepla | Phainopepla nitens | TX Canyon - Tucson |
| Pyrrhuloxia | Catdinalis sinuatus | TX Canyon, East of Willcox |
| Red-tailed hawk | Buteo jamaicensis | Ubiquitous |
| Rock dove | Columba livia | Ubiquitous |
| Song sparrow | melospiza melodia | Ubiquitous |
| White-crowned sparrow | Zonotrichia atricapilla | TX Canyon |
| | Mammals | |
| Desert cottontail | Sylvilagus auduboni | Ubiquitous |

| Common Name | Scientific Name | Location |
|-----------------------|-------------------------|------------------------|
| Muledeer | Odocoileus hemionus | Ubiquitous |
| | NEW MEXICO | |
| | Birds | |
| American kestrel | Falco sparverius | Grasslands |
| Chihuahuan raven | Corvus cryptoleucus | Ubiquitous |
| Curve-billed thrasher | Toxostoma curvirostre | Akali flats grasslands |
| Brown-headed cowbird | Molothrus ater | Agriculture |
| Gambel's quail | Callipela californica | Ubiquitous |
| Golden eagle | Aquila chrysaetos | Mesquite desert |
| Greater roadrunner | Geococcyx californianus | Ubiquitous |
| Harris hawk | Parabuteo unicinctus | Grasslands |
| House finch | Carpodacus mexicanus | West of Deming |
| Killdeer | Charadrius vociferous | Agriculture |
| Loggerhead shrike | Lanius excubitor | Grasslands |
| Meadowlark | Sturnella neglecta | Ubiquitous |
| Mexican Mallard | Anas platyrhynchos | Playas |
| Morning dove | Zenaida macroura | Ubiquitous |
| Mountain bluebird | Sialia currucoides | East of Deming |
| Northern harrier | Circus cyaneus | Grasslands |
| Red-tailed hawk | Buteo jamaicensis | Ubiquitous |
| Rock dove | Columba livia | Ubiquitous |
| Scaled quail | Callipepla squamata | Mesquite desert |
| Song sparrow | Melospiza melodia | Ubiquitous |
| Turkey vulture | Cathartes aura | East of Deming |
| White-wing dove | Zenaida asiatica | East of Deming |
| | Mammals | |
| Black-tail jackrabbit | Lepus californicus | Ubiquitous |
| Coyote | Canis latrans | Ubiquitous |
| Desert cottontail | Sylilagus auduboni | Ubiquitous |
| Striped skunk | Mephitis mephitis | Akela Flats |
| | TEXAS | |
| | Birds | |
| Greater roadrunner | Geococcyx californianus | Ubiquitous |
| Morning dove | Zenaida macroura | Ubiquitous |

| Common Name | Scientific Name | Location |
|-----------------------|--------------------|-----------------|
| Red-tailed hawk | Buteo jamaicensis | Ubiquitous |
| Rock dove | Columba livia | Ubiquitous |
| | Mammals | |
| Black-tail jackrabbit | Lepus californicus | Ubiquitous |
| | Reptiles | |
| Desert tortoise | Gopherus agassizi | Mesquite desert |

Major Soil Types – Link Two

| | | | Appendix F | l-3 | | | | | |
|-----------------------|--|--|---|-----------------------------------|--|--|---|------------------------------|---------------------|
| | | Major S | Soil Types— | -Link Two | | | | | |
| Soil Map Number | Soil Survey Name (italics)/ General Soil Map Unit | Description | USDA Texture | Unified Soil Classification | Limitations on Shallow Excavations | Suitability for Terraces and Diversions | Erosion Factor K (soil loss rate) | Wind Erodibility Group | Hydrologic Group |
| Dona A | na County, NM | | | | | | | • | |
| 5 | Pintura-Wink | Deep, nearly level to undulating, well drained and somewhat excessively drained soils that formed in alluvium modified by wind. Found on fans, terraces, and ridges. | Loamy fine sand, fine sand | SP-SM, SM | Pintura - severe, cutbanks cave; Wink - slight | Too sandy, erodes easily, soil blowing | 0.20 | 2 - 3 | A - B |
| 10 | Harrisburg-Simona-Wink | Shallow to deep, gently undulating to undulating, well drained soils that formed in residuum from sandstone, eolian material, and alluvium modified by wind; found on mesas, plains, ridges, and fans. | Sandy loam, fine sandy loam | SM | Severe, cemented pan | Cemented pan, soil blowing | 0.17-0.37 | 2 - 3 | C - D |
| 9 | Cacique-Cruces | Shallow to moderately deep, nearly level to gently sloping, well-drained soils that formed in alluvium. Found on basin floors. | Loamy sand, sandy loam | SM, SC | Severe, cemented pan | Cemented pan, soil blowing | 0.15-0.32 | 2 | С |
| 6 | Berino-Dona Ana | Deep, gently undulating to undulating, well-drained soils that formed in alluvium and alluvium modified by wind. Found on fans, piedmonts, and valley and basin floors. | Fine sandy loam, sandy clay loam | SM, SC | Slight | Soil blowing | 0.17-0.24 | 2 - 3 | В |
| 13 | Rock outcrop-Torriorthents | Rock outcrop and shallow to deep, hilly to extremely steep, well-drained soils that formed in alluvium and colluvium. Found on mountains. | Gravelly, cobbly, and stony, coarse to fine. | Not rated | Not rated | Not rated | Not rated | Not rated | Not rated |
| | | Luna | a Count | y, NM | | | | | |
| 7 | Mimbres | Deep, moderately fine textured, level to nearly level soils on basin floors and alluvial fans. | Silty clay loam, loam | CL, CL-ML | Slight, severe where flooded | Clayey; moderately slow permeability; moderate shrink- swell | Not rated | Not rated | С |
| 3 | Mohave-Stellar | Deep, moderately fine textured, nearly level to gently undulating soils on alluvial fans. | Sandy clay loam, silty clay loam | CL, ML | Moderate, clay loam material | Moderate soil blowing, moderately slow permeability | Not rated | Not rated | B - C |

| | | | Appendix F | I-3 | | | | | |
|-----------------------|--|--|--|-----------------------------------|--|--|---|------------------------------|---------------------|
| | , | Major . | Soil Types— | -Link Two | | | | | |
| Soil Map Number | Soil Survey Name (italics)/ General Soil Map Unit | Description | USDA Texture | Unified Soil Classification | Limitations on Shallow Excavations | Suitability for Terraces and Diversions | Erosion Factor K (soil loss rate) | Wind Erodibility Group | Hydrologic Group |
| 6 | Hondale-Mimbres | Deep, moderately fine to coarse textured, nearly level to gently sloping soils on alkali flats. | Loam | ML, CL | Slight | Clayey; high shrink swell; subject to piping | Not rated | Not rated | C - D |
| 4 | Bluepoint-Onite | Deep, coarse-textured, nearly level to undulating soils on alluvial fans. | Loamy sand | SM, SP-SM | Severe, subject to slumping | Very erodible; subject to piping | Not rated | Not rated | A - B |
| 5 | Pintura-Berino-Simona | Shallow to deep, coarse-textured, nearly level to undulating, hummocky soils on alluvial fans. | Loamy sand | SM, SC | Slight | Severe soil blowing hazard | Not rated | Not rated | В |
| Grant (| County, NM | | • | | | | | | |
| 4 | Stellar-Mohave-Bucklebar | Nearly level to gently sloping, well-drained, deep soils; on alluvial fans and plains. | Sandy clay loam, sandy loam | SM, ML | Slight to moderate (Stellar) too clayey | Stellar, Mohave - favorable; Bucklebar - erodes easily, soil blowing | 0.24-0.38 | 3 - 5 | B - C |
| Hidalgo | County, NM | | • | | | | | | |
| 7 | Hondale-Playas | Deep, moderately fine textured and fine textured, nearly level to gently sloping soils on alkali flats. | Silt loam | ML | Not rated | Not rated | Not rated | Not rated | D |
| 5 | Nickel-Upton-Tres Hermanos | Very shallow to deep, medium-textured and moderately fine textured, gently sloping to very steep, limy soils on uplands. | Gravelly loam, gravelly clay loam | GC, GM, SM, CL | Not rated | Not rated | Not rated | Not rated | B - D |
| 6 | Rough Broken Land-Rock land-Lehmans | Very shallow to shallow, moderately fine textured, gently sloping to very steep, rocky and stony soils, rough broken land, and rock land on hills and mountains. | Stony clay loam; gravel or cobbles | ML, CL | Not rated | Not rated | Not rated | Not rated | D |
| San Sir | mon Area, AZ | | | | | | | | |
| 6 | Tubac-Sonoita-Signal | Very deep, well drained soils on valley side slopes, alluvial fans, and terraces. | Sandy clay loam, gravelly sandy loam, gravelly loam | SC, SM-SC, GM | Tubac – moderate, too clayey; Sonoita - slight; Signal - severe - slope | Percolates slowly, soil blowing | 0.17-0.37 | 3 - 5 | B - C |

Major Soil Types—Link Two

| Soil Map Number | Soil Survey Name (italics)/ General Soil Map Unit | Description | USDA Texture | Unified Soil Classification | Limitations on Shallow Excavations | Suitability for Terraces and Diversions | Erosion Factor K (soil loss rate) | Wind Erodibility Group | Hydrologic Group |
|-----------------------|--|--|--|-----------------------------------|---|---|---|------------------------------|---------------------|
| 2 | Hondale-Bluepoint-Gothard | Very deep, somewhat excessively drained to moderately well drained, saline and sodic soils on dunes, alluvial fans, and terraces. | Loam, loamy sand, fine loamy sand | ML, SM | Hondale – moderate, too clayey; Bluepoint - severe, cutbanks cave; Gothard - slight | Hondale – per- colates slowly; Bluepoint - too sandy, soil blow- ing; Gothard - percolates slow- ly, soil blowing, erodes easily | 0.15-0.43 | 2 - 4L | A - D |
| Willcox | Area, AZ | | | | | | | | |
| 1 | Gothard-Crot-Stewart | Nearly level, moderately well drained and somewhat poorly drained, deep to very shallow, very slowly permeable, saline-alkali affected soils | Fine sandy loam, sandy loam, light loam | SM, ML | Not rated | Not rated | Not rated | Not rated | D |

KEY AND EXPLANATION OF FACTORS

USDA Texture: Particle sizes – clay and silt = <0.074 millimeter (mm) (defined by size **and** behavior); sand = 0.074 to 4.75 mm; gravel = 4.75 to 75 mm; loam = mixture of 7-27% clay + 28-50% silt + <52% sand.

Unified Soil Classification: CL = low plasticity clays, GC = clayey gravels, GM = silty gravels, ML = inorganic silts and very fine sands, SC = clayey sands, SM = silty sands, SP = poorly graded sands, gravelly sands, little or no fines.

Erosion Factor, K – K is used to estimate erosion using the Revised Universal Soil Loss Equation (RUSLE). K values reflect the rate of soil loss per rainfall-runoff (R) erosion index [ton * acre * h(hundreds of acre * foot * tonf * in)-1]. Values of K vary from 0.05 to 0.65. Fine-textured clays have low K values of 0.05 to 0.15 because the particles are resistant to detachment. Coarse-textured soils, such as sands, have low K values of 0.05 to 0.20 even though particles are easily detached because of high infiltration capacity that results in low runoff. Medium-textured soils such as silt loam have moderate K values of 0.25 to 0.45 because the soils are moderately susceptible to detachment and lower infiltration capacity produces moderate runoff. Soils with high silt content have the highest K values (0.45 to 0.65) because silt particles are easy to detach and silt soils tend to crust, producing high levels of runoff (Toy, T.J. and Foster, G.R 1998)

Wind Erodibility Groups are used to predict the susceptibility of the soil to blowing. Groups 1 (sands), 2 (loamy sands), and 3 (sandy loams) are very highly erodible to highly erodible. Groups 4L (calcareous loamy soils) and 4 (clays and clay loams) are erodible but crops can be grown if erosion control measures are used. Group 5, 6, and 7 soils (various types of loams) are slightly erodible to very slightly erodible. Group 8 soils (stony or gravelly soils) are not subject to soil blowing.

Hydrologic Groups are used to estimate runoff from precipitation. Group A soils have a high infiltration rate and therefore a low runoff potential. Group B soils have a moderate infiltration rate. Group C soils have a slow infiltration rate. Group D soils have a very slow infiltration rate and therefore the highest runoff potential.

Onan Cummins 350DFCC Generator Set Data Sheets



350DFCC ONAN GENERATOR SET

EXHAUST EMISSION DATA SHEET

ENGINE

Model:CumminsNTA855-G3Bore:5.5in. (140 mm)Type:4 Cycle, In-Line6 CylinderDieselStroke6in. (152 mm)Aspiration:Turbocharged and AftercooledDisplacement:855cu. in. (14.0 liters)

Compression Ratio: 14:1

Emission Control Device: Turbocharger and Aftercooler, with Variable Timing

| PERFORMANCE DATA | STANDBY | PRIME |
|-------------------------------|---------|-------|
| BHP @ 1800 RPM (60 Hz) | 535 | 480 |
| Fuel Consumption (gal/Hr) | 25.3 | 22.9 |
| Exhaust Gas Flow (CFM) | 3190 | 2785 |
| Exhaust Gas Temperature (°F) | 980 | 970 |

| EXHAUST EMISSION DATA | (All Values are Grams per HP-Hour) | | | |
|------------------------------------|------------------------------------|-------|--|--|
| COMPONENT | STANDBY | PRIME | | |
| HC (Total Unburned Hydrocarbons) | 0.30 | 0.25 | | |
| NOx (Oxides of Nitrogen as NO2) | 9.25 | 8.55 | | |
| CO (Carbon Monoxide) | 2.25 | 1.50 | | |
| PM (Particulate Matter) | 0.17 | 0.13 | | |
| SO ₂ (Sulfur Dioxide) | 0.59 | 0.59 | | |

TEST CONDITIONS

Data was recorded during steady-state rated engine speed (\pm 25 RPM) with full load (\pm 2%).

Pressures, temperatures, and emission rates were stablized.

Fuel Specification: ASTM D975 No. 2-D diesel fuel with 0.2% sulfur content (by weight),

and 42-50 cetane number.

Fuel Temperature: 99 \pm 9 ° F (at fuel pump inlet)

Intake Air Temperature: 77 ± 9 ° F

Barometric Pressure: 29.6 ± 1 in. Hg

Humidity: NOx measurement corrected to 75 grains H2O/lb dry air

The NOx, HC, CO and PM emission data tabulated here were taken from a single engine under the test conditions shown above. Data for the other components are estimated. These data are subject to instrumentation, and engine to engine variability. Engine operation with excessive air intake or exhaust restriction beyond published maximum limits, or with improper maintenance, may result in elevated emission levels.


Onan Corporation

Data and Specifications Subject to Change Without Notice.


EDS - 114C



Measured Sound Performance 350 DFCC 60 Hz



MEASURED SOUND LEVELS - 60 HZ



- Note:
 1. All positions 23 Feet (7m) from perimeter of genset.
 2. Unhoused genset operating at full load
 3. Does not include exhaust noise.
 4. Test conducted on 100 foot diameter asphalt surface.

Drawing Reference Number: 178-0391

Onan is a registered trademark of Onan Corporation

Cummins is a registered trademark of Cummins Engine Company

©1994 Onan Corporation Printed in USA.

1/94 Bulletin MSP-116

SCREEN MODEL OUTPUT LISTINGS

```
04/18/00
                                                                                      19:22:10
  *** SCREEN3 MODEL RUN ***
  *** VERSION DATED 96043 ***
 El Paso Tucson Backup Generator CO Emissions
 SIMPLE TERRAIN INPUTS:
    SOURCE TYPE
    EMISSION RATE (G/S) =
                                        .334400
                                         3.6600
    STACK HEIGHT (M)
    STK INSIDE DIAM (M)
    STK EXIT VELOCITY (M/S)=
                                        46.4245
    STK GAS EXIT TEMP (K) =
                                     800.0000
    AMBIENT AIR TEMP (K) =
                                        291.0000
    RECEPTOR HEIGHT (M)
    URBAN/RURAL OPTION
                                           URBAN
    BUILDING HEIGHT (M)
                               =
                                          .0000
    MIN HORIZ BLDG DIM (M) =
                                            .0000
    MAX HORIZ BLDG DIM (M) =
                                            .0000
THE REGULATORY (DEFAULT) MIXING HEIGHT OPTION WAS SELECTED.
THE REGULATORY (DEFAULT) ANEMOMETER HEIGHT OF 10.0 METERS WAS ENTERED.
    STACK EXIT VELOCITY WAS CALCULATED FROM
     VOLUME FLOW RATE = 3190.0000 (ACFM)
 BUOY. FLUX = 2.990 \text{ M**} \frac{4}{\text{S**}}3; MOM. FLUX = 8.093 \text{ M**} \frac{4}{\text{S**}}2.
 *** FULL METEOROLOGY ***
 *********
 *** SCREEN AUTOMATED DISTANCES ***
 *** TERRAIN HEIGHT OF 0. M ABOVE STACK BASE USED FOR FOLLOWING DISTANCES ***
   DIST
             CONC
                                  U10M USTK MIX HT PLUME SIGMA SIGMA
    (M) (UG/M**3) STAB (M/S) (M/S) (M) HT (M) Y (M) Z (M) DWASH
   10. .5028 3 10.0 10.0 3200.0 8.53 2.27 2.08 100. 62.63 4 4.0 4.0 1280.0 15.84 16.07 14.23 200. 36.50 4 2.0 2.0 640.0 28.02 31.57 28.07 300. 31.44 6 1.0 1.0 10000.0 39.11 32.79 22.36 400. 33.13 6 1.0 1.0 10000.0 39.11 42.09 27.25 500. 30.72 6 1.0 1.0 10000.0 39.11 51.22 31.89 600. 27.29 6 1.0 1.0 10000.0 39.11 60.13 36.27 700. 23.96 6 1.0 1.0 10000.0 39.11 60.13 36.27 700. 23.96 6 1.0 1.0 10000.0 39.11 68.81 40.40 800. 21.06 6 1.0 1.0 10000.0 39.11 77.26 44.32 900. 18.60 6 1.0 1.0 10000.0 39.11 85.49 48.05 1000. 16.55 6 1.0 1.0 10000.0 39.11 93.52 51.60
                                                                                             NO
                                                                                             NO
   800. 21.06
900. 18.60
1000. 16.55
                                                                                            NΟ
                                                                                             NO
MAXIMUM 1-HR CONCENTRATION AT OR BEYOND 10. M:
     30. 98.49 3 10.0 10.0 3200.0 8.53
                                                                       6.81 6.23
                                                                                           NO
  DWASH= MEANS NO CALC MADE (CONC = 0.0)
  DWASH=NO MEANS NO BUILDING DOWNWASH USED
  DWASH=HS MEANS HUBER-SNYDER DOWNWASH USED
  DWASH=SS MEANS SCHILLMAN-SCIRE DOWNWASH USED
  DWASH=NA MEANS DOWNWASH NOT APPLICABLE, X<3*LB
       *** SUMMARY OF SCREEN MODEL RESULTS ***
       **********
                                       DIST TO TERRAIN
  CALCULATION
                       MAX CONC
                      (UG/M**3) MAX (M) HT (M)
 SIMPLE TERRAIN
                       98.49
                                           30.
```

```
** REMEMBER TO INCLUDE BACKGROUND CONCENTRATIONS **
***************
04/18/00
                                                                                                                   19:19:29
   *** SCREEN3 MODEL RUN ***
   *** VERSION DATED 96043 ***
 El Paso Tucson Backup Generator NOX Emissions
 SIMPLE TERRAIN INPUTS:
      SOURCE TYPE
                                                        POINT
      EMISSION RATE (G/S) = 1.37470
                                                     3.6600
      STACK HEIGHT (M)
      STK INSIDE DIAM (M)
                                                          . 2032
                                                     46.4245
      STK EXIT VELOCITY (M/S)=
      STK GAS EXIT TEMP (K) = 800.0000
      AMBIENT AIR TEMP (K) =
                                                    291.0000
      RECEPTOR HEIGHT (M)
      URBAN/RURAL OPTION
                                                         URBAN
                                                        .0000
      BUILDING HEIGHT (M)
                                        =
      MIN HORIZ BLDG DIM (M) =
                                                          .0000
      MAX HORIZ BLDG DIM (M) =
                                                           .0000
 THE REGULATORY (DEFAULT) MIXING HEIGHT OPTION WAS SELECTED.
 THE REGULATORY (DEFAULT) ANEMOMETER HEIGHT OF 10.0 METERS WAS ENTERED.
      STACK EXIT VELOCITY WAS CALCULATED FROM
      VOLUME FLOW RATE = 3190.0000 (ACFM)
                        2.990 M^{**4}/S^{**3}; MOM. FLUX = 8.093 M^{**4}/S^{**2}.
  *** FULL METEOROLOGY ***
  *********
  *** SCREEN AUTOMATED DISTANCES ***
  **********
 *** TERRAIN HEIGHT OF 0. M ABOVE STACK BASE USED FOR FOLLOWING DISTANCES ***
                                             U10M USTK MIX HT PLUME SIGMA SIGMA
   DIST
                  CONC
      (M) \qquad (UG/M**3) \qquad STAB \qquad (M/S) \qquad (M/S) \qquad (M) \qquad HT \qquad (M) \qquad Y \qquad (M) \qquad Z \qquad (M) \qquad DWASH 

      10.
      2.067
      3
      10.0
      10.0
      3200.0
      8.53
      2.27
      2.08

      100.
      257.5
      4
      4.0
      4.0
      1280.0
      15.84
      16.07
      14.23

      200.
      150.0
      4
      2.0
      2.0
      640.0
      28.02
      31.57
      28.07

      300.
      129.2
      6
      1.0
      1.0
      10000.0
      39.11
      32.79
      22.36

      400.
      136.2
      6
      1.0
      1.0
      10000.0
      39.11
      42.09
      27.25

      500.
      126.3
      6
      1.0
      1.0
      10000.0
      39.11
      51.22
      31.89

      600.
      112.2
      6
      1.0
      1.0
      10000.0
      39.11
      60.13
      36.27

      700.
      98.52
      6
      1.0
      1.0
      10000.0
      39.11
      68.81
      40.40

      800.
      86.57
      6
      1.0
      1.0
      10000.0
      39.11
      77.26
      44.32

      900.
      76.48
      6
      1.0
      1.0
      10000.0
      39.11
      85.49
      48.05

      1000.

                                                                                                                           NO
                                                                                                                            NO
                                                                                                                          NO
                                                                                                                           NO
 MAXIMUM 1-HR CONCENTRATION AT OR BEYOND
                                                                     10. M:
       30. 404.9 3 10.0 10.0 3200.0 8.53 6.81 6.23
                                                                                                                        NO
```

DWASH= MEANS NO CALC MADE (CONC = 0.0) DWASH=NO MEANS NO BUILDING DOWNWASH USED DWASH=HS MEANS HUBER-SNYDER DOWNWASH USED DWASH=SS MEANS SCHULMAN-SCIRE DOWNWASH USED

********* *** SUMMARY OF SCREEN MODEL RESULTS *** *********

DWASH=NA MEANS DOWNWASH NOT APPLICABLE, X<3*LB

| CALCULATION | MAX CONC | DIST TO | TERRAIN |
|----------------|-----------|---------|---------|
| PROCEDURE | (UG/M**3) | MAX (M) | HT (M) |
| | | | |
| SIMPLE TERRAIN | 404.9 | 30. | 0. |

^{**} REMEMBER TO INCLUDE BACKGROUND CONCENTRATIONS **

STK INSIDE DIAM (M) = .2032

STK EXIT VELOCITY (M/S) = 46.4245

STK GAS EXIT TEMP (K) = 800.0000

AMBLENT AIR TEMP (K) = 291.0000

RECEPTOR HEIGHT (M) = .0000

URBAN/RURAL OPTION = URBAN

BUILDING HEIGHT (M) = .0000

MIN HORIZ BLDG DIM (M) = .0000

MAX HORIZ BLDG DIM (M) = .0000

THE REGULATORY (DEFAULT) MIXING HEIGHT OPTION WAS SELECTED. THE REGULATORY (DEFAULT) ANEMOMETER HEIGHT OF 10.0 METERS WAS ENTERED.

STACK EXIT VELOCITY WAS CALCULATED FROM VOLUME FLOW RATE = 3190.0000 (ACFM)

BUOY. FLUX = 2.990 M**4/S**3; MOM. FLUX = 8.093 M**4/S**2.

*** FULL METEOROLOGY ***

*** TERRAIN HEIGHT OF 0. M ABOVE STACK BASE USED FOR FOLLOWING DISTANCES ***

| DIST | CONC | | U10M | USTK | MIX HT | PLUME | SIGMA | SIGMA | |
|-------|-----------|------|-------|-------|---------|--------|-------|-------|-------|
| (M) | (UG/M**3) | STAB | (M/S) | (M/S) | (M) | HT (M) | Y (M) | Z (M) | DWASH |
| | | | | | | | | | |
| 10. | .3804E-01 | 3 | 10.0 | 10.0 | 3200.0 | 8.53 | 2.27 | 2.08 | NO |
| 100. | 4.738 | 4 | 4.0 | 4.0 | 1280.0 | 15.84 | 16.07 | 14.23 | NO |
| 200. | 2.761 | 4 | 2.0 | 2.0 | 640.0 | 28.02 | 31.57 | 28.07 | NO |
| 300. | 2.379 | 6 | 1.0 | 1.0 | 10000.0 | 39.11 | 32.79 | 22.36 | NO |
| 400. | 2.507 | 6 | 1.0 | 1.0 | 10000.0 | 39.11 | 42.09 | 27.25 | NO |
| 500. | 2.324 | 6 | 1.0 | 1.0 | 10000.0 | 39.11 | 51.22 | 31.89 | NO |
| 600. | 2.065 | 6 | 1.0 | 1.0 | 10000.0 | 39.11 | 60.13 | 36.27 | NO |
| 700. | 1.813 | 6 | 1.0 | 1.0 | 10000.0 | 39.11 | 68.81 | 40.40 | NO |
| 800. | 1.593 | 6 | 1.0 | 1.0 | 10000.0 | 39.11 | 77.26 | 44.32 | NO |
| 900. | 1.408 | 6 | 1.0 | 1.0 | 10000.0 | 39.11 | 85.49 | 48.05 | NO |
| 1000. | 1.252 | 6 | 1.0 | 1.0 | 10000.0 | 39.11 | 93.52 | 51.60 | NO |

MAXIMUM 1-HR CONCENTRATION AT OR BEYOND 10. M: 30. 7.451 3 10.0 10.0 3200.0 8.53 6.81 6.23 NO

DWASH= MEANS NO CALC MADE (CONC = 0.0)
DWASH=NO MEANS NO BUILDING DOWNWASH USED
DWASH=HS MEANS HUBER-SNYDER DOWNWASH USED
DWASH=SS MEANS SCHULMAN-SCIRE DOWNWASH USED
DWASH=NA MEANS DOWNWASH NOT APPLICABLE, X<3*LB

| CALCULATION | MAX CONC | DIST TO | TERRAIN |
|----------------|-----------|---------|---------|
| PROCEDURE | (UG/M**3) | MAX (M) | HT (M) |
| | | | |
| SIMPLE TERRAIN | 7.451 | 30. | 0. |

04/18/00

19:24:21

```
*** SCREEN3 MODEL RUN ***
  *** VERSION DATED 96043 ***
El Paso Tucson Backup Generator SO2 Emissions
SIMPLE TERRAIN INPUTS:
    SOURCE TYPE
                                         POINT
    EMISSION RATE (G/S) = .880000E-01
                                       3.6600
    STACK HEIGHT (M) = STK INSIDE DIAM (M) =
                                          .2032
    STK EXIT VELOCITY (M/S)=
   STK GAS EXIT TEMP (K) = 800.0000

AMBIENT AIR TEMP (K) = 291.0000

RECEPTOR HEIGHT (M) = .0000
    URBAN/RURAL OPTION
                                         URBAN
                                         .0000
    BUILDING HEIGHT (M)
    MIN HORIZ BLDG DIM (M) =
                                          .0000
    MAX HORIZ BLDG DIM (M) =
                                          .0000
THE REGULATORY (DEFAULT) MIXING HEIGHT OPTION WAS SELECTED.
THE REGULATORY (DEFAULT) ANEMOMETER HEIGHT OF 10.0 METERS WAS ENTERED.
    STACK EXIT VELOCITY WAS CALCULATED FROM
    VOLUME FLOW RATE = 3190.0000
                                              (ACFM)
BUOY. FLUX = 2.990 \text{ M**} \frac{4}{\text{S**3}}; MOM. FLUX = 8.093 \text{ M**} \frac{4}{\text{S**2}}.
 *** FULL METEOROLOGY ***
 *** SCREEN AUTOMATED DISTANCES ***
 **********
 *** TERRAIN HEIGHT OF
                              0. M ABOVE STACK BASE USED FOR FOLLOWING DISTANCES ***
  DIST
            CONC
                                  U10M USTK MIX HT PLUME SIGMA SIGMA
   (M) (UG/M**3) STAB (M/S) (M/S) (M) HT (M) Y (M) Z (M) DWASH
  10. .1323 3 10.0 10.0 3200.0 8.53 2.27 2.08 NO
100. 16.48 4 4.0 4.0 1280.0 15.84 16.07 14.23 NO
200. 9.604 4 2.0 2.0 640.0 28.02 31.57 28.07 NO
300. 8.273 6 1.0 1.0 10000.0 39.11 32.79 22.36 NO
400. 8.719 6 1.0 1.0 10000.0 39.11 42.09 27.25 NO
500. 8.084 6 1.0 1.0 10000.0 39.11 51.22 31.89 NO
600. 7.181 6 1.0 1.0 10000.0 39.11 60.13 36.27 NO
700. 6.307 6 1.0 1.0 10000.0 39.11 68.81 40.40 NO
800. 5.542 6 1.0 1.0 10000.0 39.11 77.26 44.32 NO
900. 4.896 6 1.0 1.0 10000.0 39.11 85.49 48.05 NO
1000. 4.355 6 1.0 1.0 10000.0 39.11 93.52 51.60 NO
MAXIMUM 1-HR CONCENTRATION AT OR BEYOND
                                                   10. M:
                     3 10.0 10.0 3200.0 8.53
     30. 25.92
                                                                     6.81 6.23
                                                                                           NO
  DWASH= MEANS NO CALC MADE (CONC = 0.0)
  DWASH=NO MEANS NO BUILDING DOWNWASH USED
 DWASH=HS MEANS HUBER-SNYDER DOWNWASH USED
 DWASH=SS MEANS SCHULMAN-SCIRE DOWNWASH USED
 DWASH=NA MEANS DOWNWASH NOT APPLICABLE, X<3*LB
       **********
      *** SUMMARY OF SCREEN MODEL RESULTS ***
      ***********
 CALCULATION
                       MAX CONC
                                      DIST TO TERRAIN
   PROCEDURE
                     (UG/M**3)
                                       MAX (M)
                                                   HT (M)
                      _____
  _____
SIMPLE TERRAIN
                      25.92
                                          30.
***************
 ** REMEMBER TO INCLUDE BACKGROUND CONCENTRATIONS **
```